



GENERAL PURPOSE HOSE

BY

50TH
ANNIVERSARY

Recommended For: Air and water applications requiring maximum flexibility and outstanding resistance to heat, water and oil.

Construction Tube: Type P (EPDM) Black.

Reinforcement: Synthetic, high tensile textile cord.

Cover: Type P (EPDM) Black.

Colors: Black only.



Temperature Range: -40°C to 93°C (-40°F to 200°F)

Hose I.D.	Hose O.D.	Hose Color	Recommended Working Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Inches of Mercury	*Approx. Reel Quantity	Part No.	Quantity Pricing	
									1-99 Ft.	100+ Ft.
1/4"	.47"	Black	200 P.S.I.	600 P.S.I.	3"	30	500'	4GP	\$.76 ft.	\$.73 ft.
3/8"	.66"	Black	200 P.S.I.	600 P.S.I.	3"	30	500'	6GP	\$1.06 ft.	\$1.01 ft.
1/2"	.81"	Black	200 P.S.I.	600 P.S.I.	5"	25	500'	8GP	\$1.26 ft.	\$1.20 ft.
5/8"	.93"	Black	200 P.S.I.	600 P.S.I.	6"	20	500'	10GP	\$1.53 ft.	\$1.46 ft.
3/4"	1.08"	Black	200 P.S.I.	600 P.S.I.	6"	15	500'	12GP	\$1.83 ft.	\$1.75 ft.
1"	1.48"	Black	200 P.S.I.	600 P.S.I.	8"	10	400'	16GP	\$3.15 ft.	\$3.00 ft.
1-1/4"	1.78"	Black	200 P.S.I.	600 P.S.I.	10"	10	200'	20GP	\$4.55 ft.	\$4.30 ft.
1-1/2"	1.98"	Black	200 P.S.I.	600 P.S.I.	12"	10	200'	24GP	\$5.70 ft.	\$5.35 ft.



LOCK-ON HOSE

QUALITY BY

HIGHER PRESSURE RATING

Recommended For: Petroleum-base hydraulic oils, antifreeze solutions, water, hot lubricating oils, diesel fuels and air. Lock-On hose and couplings are not recommended for vibration or pressure surge applications or for critical applications, such as permanent piping in residential or commercial buildings.

Tube: Black, oil resistant synthetic rubber highly resistant to oil and heat.

Reinforcement: One fiber braid.

Cover: Oil and abrasion resistant synthetic rubber.

Colors: Red and Blue



COMPARABLE TO PARKER 801 HOSE

Temperature Range: -40°C to 100°C (-40°F to 212°F)

Water: 71°C (160F) ONLY.

Hose I.D.	Hose O.D.	Hose Color	Recommended Working Pressure	Minimum Burst Pressure	Minimum Bend Radius	Vacuum Inches of Mercury	*Approx. Reel Quantity	Part No.	Quantity Pricing	
									1-99 Ft.	100+ Ft.
1/4"	.47"	Blue	300 P.S.I.	1200 P.S.I.	3"	28	475'	4LOLB	\$1.75 ft.	\$1.69 ft.
1/4"	.47"	Red	300 P.S.I.	1200 P.S.I.	3"	28	475'	4LOLR	\$1.75 ft.	\$1.69 ft.
3/8"	.61"	Blue	300 P.S.I.	1200 P.S.I.	3"	28	300'	6LOLB	\$1.95 ft.	\$1.86 ft.
3/8"	.61"	Red	300 P.S.I.	1200 P.S.I.	3"	28	300'	6LOLR	\$1.95 ft.	\$1.86 ft.
1/2"	.75"	Blue	300 P.S.I.	1200 P.S.I.	5"	28	300'	8LOLB	\$2.35 ft.	\$2.25 ft.
1/2"	.75"	Red	300 P.S.I.	1200 P.S.I.	5"	28	300'	8LOLR	\$2.35 ft.	\$2.25 ft.
5/8"	.91"	Blue	300 P.S.I.	1200 P.S.I.	6"	28	250'	10LOLB	\$3.30 ft.	\$3.15 ft.
5/8"	.91"	Red	300 P.S.I.	1200 P.S.I.	6"	28	250'	10LOLR	\$3.30 ft.	\$3.15 ft.
3/4"	1.04"	Blue	300 P.S.I.	1200 P.S.I.	7"	15	225'	12LOLB	\$4.20 ft.	\$4.00 ft.
3/4"	1.04"	Red	300 P.S.I.	1200 P.S.I.	7"	15	225'	12LOLR	\$4.20 ft.	\$4.00 ft.

* Note: A full reel may contain up to three pieces.



PLASTIC PROCESS EQUIPMENT, INC.

8303 CORPORATE PARK DRIVE
MACEDONIA, OHIO 44056-2300
216-367-7000 • FAX: 216-367-7022
TOLL FREE: 800-321-0562

6385 MONTESSOURI STREET
LAS VEGAS, NEVADA 89113-1186
702-433-6385 • FAX: 702-433-6388
TOLL FREE: 800-258-8877

www.ppe.com
e-mail: sales@ppe.com

Toll Free: USA, Canada & Mexico
800-362-0706

Order Fax: 800-223-8305