



PUSH-LOK® PLUS INDUSTRIAL HOSE

AIR - WATER - OIL • RATED 200 TO 350 P.S.I.



5 COLORS AVAILABLE!
BLACK-RED-BLUE-YELLOW-GRAY

ISO-9001
MANUFACTURED IN A
QUALITY SYSTEM CERTIFIED
FACILITY.

IMPROVED QUALITY
BY PARKER

801 PUSH-LOK Plus HOSE

SPIRALLY REINFORCED

CONSTRUCTION: Synthetic rubber liner, one spiral fiber braid reinforcement, synthetic rubber cover.

APPLICATIONS: Widely used for shop air systems and general industrial, maintenance and automotive applications for air, water, gasoline, diesel fuels, lubricating oils and anti-freeze.

TEMPERATURE RANGE:

- Petroleum base hydraulic fluid, lubricating oils and anti-freeze solutions -40°F to 257°F (-40°C to +125°C)
- Diesel fuels -40°F to 257°F (-40°C to +125°C) with HY fittings only.
- Water, water/oil emulsion and water glycol fluids up to 185°F (85°C)
- Air up to 158°F (70°C)

Colors: For color coding applications, PUSH-LOK Plus 801 Hose is furnished with BLACK, RED, BLUE, YELLOW or GRAY cover. Add BK for black, R for red, B for blue, Y for yellow or G for gray after part number.



HEAVY DUTY

Parker 801 PUSH-LOK Plus Hose is the finest quality low cost hose available. It is ideal for on-the-job quick hose replacements as it can be used with PUSH-LOK or standard fittings with clamps. PUSH-LOK Plus is now compatible with Parker HY Series Parkrimp fittings and 82 Series field attachable fittings.

*Add BK for black, R for red, B for blue, Y for yellow or G for gray after part number.

Hose I.D.	Hose O.D.	Recommended Working Pressure P.S.I.	Minimum Burst Pressure P.S.I.	Minimum Bend Radius In.	Vacuum Inches of Mercury	† Approx. Reel Quantity	Part No.*	QUANTITY PRICES		
								10-99 Ft.	100+ Ft.	Full Reel†
1/4"	.50	350	1000	2-1/2"	28	600'	801-4	\$1.63 ft.	\$1.56 ft.	\$1.49 ft.
3/8"	.63	350	1000	3"	28	450'	801-6	\$1.82 ft.	\$1.74 ft.	\$1.66 ft.
1/2"	.78	300	1000	5"	28	300'	801-8	\$2.25 ft.	\$2.15 ft.	\$2.05 ft.
5/8"	.91	300	1000	6"	15	250'	801-10	\$3.75 ft.	\$3.60 ft.	\$3.45 ft.
3/4"	1.03	300	1000	7"	15	200'	801-12	\$4.70 ft.	\$4.50 ft.	\$4.30 ft.
1"	1.28	200	700	10"	15	150'	801-16	\$6.20 ft.	\$5.95 ft.	\$5.70 ft.

† Note: A full reel may contain up to three pieces. It's Parker's policy, not ours!




PUSH-LOK® INDUSTRIAL HOSE

AIR - WATER - OIL • RATED 300 P.S.I.

3 COLORS AVAILABLE
RED - BLUE - GRAY



NOTE!
Premium reinforced braid for better fitting retention.



- **CONSTRUCTION:** Black nitrile liner with one braided reinforced braid (not spiral) for better fitting retention & neoprene outer cover.
- **APPLICATIONS:** This oil resistant hose is superior for use with air tools, air systems and to convey water, mild chemicals, various petroleum products, anti-freeze, etc.
- **TEMPERATURE RANGE:** -40°F to + 212°F
- Flame resistant cover labeled MSHA Approved.
- For use with Push-Lok fittings or standard fittings w/ hose clamps.

1. Better reinforced braid (not less costly spiral braid!) for better fitting retention.
2. Better 300 P.S.I. working pressure.
3. Better lower prices.

*Add R for red, B for blue or G for gray after part number.

Hose I.D.	Hose O.D.	Recommended Working Pressure P.S.I.	Minimum Bend Radius In.	Approx. Reel Quantity	Part No.*	QUANTITY PRICES		
						10-99 Ft.	100+ Ft.	Full Reel†
1/4"	.50	300	3"	700'	7212-251	\$1.30 ft.	\$1.25 ft.	\$1.20 ft.
3/8"	.62	300	3"	700'	7212-381	\$1.66 ft.	\$1.59 ft.	\$1.52 ft.
1/2"	.75	300	5"	600'	7212-501	\$1.90 ft.	\$1.81 ft.	\$1.72 ft.
5/8"	.91	300	6"	500'	7212-631	\$2.95 ft.	\$2.80 ft.	\$2.65 ft.
3/4"	1.03	300	7"	400'	7212-751	\$3.40 ft.	\$3.25 ft.	\$3.10 ft.

† Note: A full reel may contain up to three pieces.