

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND COMPANY/UNDERTAKING

Material Name : Ethylene Glycol

Other names / Synonyms : Ethane diol 1,2

MEG Glycol

Dihydroxy ethane 1,2 Ethylene Glycol

Recommended use / Restrictions of use

Chemical intermediate. Advice in this document relates only to product as originally supplied. Other derivative chemicals will have different properties and hazards. Advice should be sought

on their safe handling and use.

Supplier : Shell Eastern Trading (PTE) Ltd

9 North Buona Vista Drive,

#07-01,

Tower 1, The Metropolis Singapore 138588

Singapore

Telephone : +65-6384 8000

Fax

: +44 (0) 151 350 4595

Emergency Telephone Number

2. HAZARDS IDENTIFICATION

GHS Classification : Acute toxicity, Category 4

Specific target organ toxicity - repeated exposure, Category 2,

Kidney.

GHS Label Elements

Symbol(s) :





Signal Words : Warning

GHS Hazard statements : PHYSICAL HAZARDS:

Not classified as a physical hazard under GHS criteria.

HEALTH HAZARDS: H302: Harmful if swallowed.

H373: May cause damage to organs or organ systems through

prolonged or repeated exposure.

Kidney.

ENVIRONMENTAL HAZARDS:

Not classified as an environmental hazard under GHS criteria.

1/10

Print Date 02.07.2014 00000001587 MSDS_SG



Safety Data Sheet

GHS Precautionary Statements

Prevention P260: Do not breathe dust/fume/gas/mist/vapours/spray.

P264: Wash hands thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P301+P312: IF SWALLOWED: Call a POISON CENTER or Response

doctor/physician if you feel unwell.

P330: Rinse mouth.

P314: Get medical advice/attention if you feel unwell.

Storage No precautionary phrases.

Disposal: P501: Dispose of contents and container to appropriate waste

site or reclaimer in accordance with local and national

regulations.

Other Hazards which do not result in classification

Not classified as flammable but will burn.

Ingestion may cause drowsiness and dizziness.

Inhalation of vapours or mists may cause irritation to the

respiratory system.

Aggravated Medical

Condition

Pre-existing medical conditions of the following organ(s) or

organ system(s) may be aggravated by exposure to this

material: Kidney.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Identity 1,2-Ethane diol. **Synonyms** : Ethane diol 1,2

> MEG Glycol

Dihydroxy ethane 1,2

Ethylene Glycol

CAS No. 107-21-1 INDEX No. 603-027-00-1 **EINECS No.** 203-473-3

Classification of components according to GHS

Chemical Name	Synonyms	CAS	Hazard Class (category)	Hazard statement	Conc.
Ethylene Glycol		107-21-1	Acute Tox., 4; STOT RE, 2;	H302;H373;	> 95.00 %W

4. FIRST-AID MEASURES

General Information Not expected to be a health hazard when used under normal

Print Date 02.07.2014 00000001587 MSDS_SG





Safety Data Sheet

conditions.

The first aid measures for different exposure routes:

Inhalation Remove to fresh air. If rapid recovery does not occur, transport

to nearest medical facility for additional treatment.

Skin Contact Remove contaminated clothing. Flush exposed area with water

and follow by washing with soap if available. If persistent

irritation occurs, obtain medical attention.

Flush eye with copious quantities of water. If persistent irritation **Eye Contact**

occurs, obtain medical attention.

DO NOT DELAY. Do not induce vomiting. If victim is alert, rinse Ingestion

mouth and drink 1/2 to 1 glass of water to help dilute the material. Do not give liquids to a drowsy, convulsing, or unconscious person. Transport to nearest medical facility for additional treatment. If vomiting occurs spontaneously, keep

head below hips to prevent aspiration.

Notes to physician **Most important** symptoms and effects, both acute and delayed

Kidney toxicity may be recognized by blood in the urine or increased or decreased urine flow. Other signs and symptoms can include nausea, vomiting, abdominal cramps, diarrhoea, lumbar pain shortly after ingestion, and possibly narcosis and death. Eye irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blurred vision. Skin irritation signs and symptoms may include a burning sensation, redness, swelling, and/or blisters. Respiratory irritation signs and symptoms may include a temporary burning sensation of the

nose and throat, coughing, and/or difficulty breathing.

Immediate medical attention, special

treatment

IMMEDIATE TREATMENT IS EXTREMELY IMPORTANT! May cause significant renal, respiratory, and CNS toxicity. May cause significant acidosis. Call a doctor or poison control center for

guidance.

5. FIRE-FIGHTING MEASURES

Specific Hazards Material will not burn unless preheated. Carbon monoxide may

> be evolved if incomplete combustion occurs. Containers exposed to intense heat from fires should be cooled with large

quantities of water.

Suitable Extinguishing

Media

Alcohol-resistant foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small

fires only.

Unsuitable Extinguishing

Media

Do not use water in a jet.

Protective Equipment for

Firefighters

Wear full protective clothing and self-contained breathing

apparatus.

Other Advice Evacuate the area of all non-essential personnel. Keep adjacent

containers cool by spraying with water.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions. **Protective Equipment and Emergency Procedures**

Avoid contact with spilled or released material. For guidance on selection of personal protective equipment see Chapter 8 of this

Material Safety Data Sheet.

3/10

Print Date 02.07.2014 000000001587 MSDS_SG





Safety Data Sheet

Environmental Precautions

: Prevent from spreading or entering into drains, ditches or rivers

by using sand, earth, or other appropriate barriers. Use appropriate containment to avoid environmental

contamination.

Ventilate contaminated area thoroughly.

Methods and Material for Containment and **Cleaning Up**

Contain run-off from residue flush and dispose of properly. Soak up residue with an absorbent such as clay, sand or other

suitable material.

For small liquid spills (< 1 drum), transfer by mechanical means to a labelled, sealable container for product recovery or safe disposal. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely. Remove

contaminated soil and dispose of safely.

For large liquid spills (> 1 drum), transfer by mechanical means such as vacuum truck to a salvage tank for recovery or safe disposal. Do not flush away residues with water. Retain as contaminated waste. Allow residues to evaporate or soak up with an appropriate absorbent material and dispose of safely.

Remove contaminated soil and dispose of safely.

Additional Advice

See Chapter 13 for information on disposal. Observe all relevant local regulations. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur. Dike and contain spill water.

7. HANDLING AND STORAGE

General Precautions

Avoid breathing vapours or contact with material. Only use in well ventilated areas. Wash thoroughly after handling. On guidance on selection of personal protective equipment see Chapter 8 of this Safety Data Sheet. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

Precautions for Safe Handling

Use local exhaust extraction over processing area. Handle and open container with care in a well-ventilated area. Do not empty into drains. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Handling Temperature: Ambient. 60 °C maximum

Conditions for Safe Storage

Tanks must be clean, dry and rust-free. Keep container tightly closed. Must be stored in a diked (bunded) well-ventilated area, away from sunlight, ignition sources and other sources of heat. Cleaning, inspection and maintenance of storage tanks is a specialist operation which requires the implementation of strict procedures and precautions. Drums should be stacked to a maximum of 3 high. Storage Temperature: Ambient. 60 °C maximum

Product Transfer

Keep containers closed when not in use. Do not pressurize drum containers to empty.

Recommended Materials

Stainless steel. Mild steel. Carbon steel

Other Advice

Ensure that all local regulations regarding handling and storage

4/10

Print Date 02.07.2014 00000001587 MSDS SG



Effective Date 25.03.2014

facilities are followed.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

If the American Conference of Governmental Industrial Hygienists (ACGIH) value is provided on this document, it is provided for information only.

Occupational Exposure Limits

Material	Source	Туре	ppm	mg/m3	Notation		
Ethylene Glycol	ACGIH	Ceiling		100 mg/m3			
Aerosol.							
	SG OE	L STEL	50 ppm	127 mg/m3			

Additional Information Wash hands before eating, drinking, smoking and using the

toilet. Launder contaminated clothing before re-use.

Biological Exposure Index (BEI)

No biological limit allocated.

Appropriate Engineering

Controls

: No exposure controls are ordinarily required under normal conditions of use. It is good general industrial hygiene practice

to minimize exposure to the material.

Individual Protection

Measures **Respiratory Protection** Personal protective equipment (PPE) should meet

recommended national standards. Check with PPE suppliers. If engineering controls do not maintain airborne concentrations

to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are unsuitable (e.g., airborne concentrations are high, risk of oxygen deficiency, confined space) use appropriate positive pressure breathing apparatus. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for combined

particulate/organic gases and vapors [Type A/Type P boiling

point > 65°C (149°F)] meeting EN14387 and EN143.

Hand Protection Where hand contact with the product may occur the use of

> gloves approved to relevant standards (e.g. Europe: EN374, US: F739, AS/NZS:2161) made from the following materials may provide suitable chemical protection: Longer term

protection: PVC. Neoprene rubber. Nitrile rubber. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material,

dexterity. Always seek advice from glove suppliers.

Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is

recommended.

Eye Protection Chemical splash goggles (chemical monogoggles).

Skin protection not ordinarily required beyond standard issue **Body protection**

Print Date 02.07.2014 000000001587 MSDS_SG





Safety Data Sheet

work clothes. Chemical resistant gloves/gauntlets, boots, and

apron.

Thermal hazards Not applicable **Monitoring Methods**

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate. Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available. National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/ Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/ Health and Safety Executive (HSE), UK: Methods for the Determination of

Hazardous Substances, http://www.hse.gov.uk/ Institut für Arbeitsschutz Deutschen Gesetzlichen

Unfallversicherung (IFA), Germany.

http://www.dguv.de/inhalt/index.jsp L'Institut National de

Recherche et de Securité, (INRS), France

http://www.inrs.fr/accueil

Environmental Exposure Controls

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations. Exhaust emission systems should be designed in accordance with local conditions: the air should always be moved away from the source of vapour generation and the person working at this point. Eye washes and showers for emergency use. Firewater monitors and deluge systems are

recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Colourless Slightly viscous liquid.

Odour : Mild

Odour threshold : Data not available. : Not applicable

Initial Boiling Point and

Boiling Range

: 244 - 250 °C / 471 - 482 °F

Melting / freezing point : -10 °C / 14 °F

Flash point

Upper / lower Flammability

: 115 - 116 °C / 239 - 241 °F(Pensky-Martens Closed Cup) : 3 - 7 %(V) 3.2 - 28 %(V)

or Explosion limits

: 225 °C / 437 °F413 °C / 775 °F Auto-ignition temperature

Flammability (solid, gas) : No, product cannot ignite due to static electricity.

< 1.3 Pa at 20 °C / 68 °F< 10 Pa at 20 °C / 68 °F Vapour pressure

Relative Density

Data not available.

Density : 1,116 kg/m3 at 20 °C / 68 °F Water solubility : at 20 °C / 68 °FCompletely Soluble

Print Date 02.07.2014 00000001587

6/10





Solubility in other solvents n-octanol/water partition coefficient (log Pow)

Decomposition temperature

: Data not available. : -1.93at 20 °C / 68 °F

: Note:: Stable under normal conditions of use., Reacts with strong

oxidising agents.

Dynamic viscosity : Data not available.

Kinematic viscosity 33 mm2/s at 20 °C / 68 °F

Vapour density (air=1) 2.14

Electrical conductivity Electrical conductivity: > 10 000 pS/m, A number of factors, for

> example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid., This material is not expected to be a static accumulator.

Stability Stable. Evaporation rate (nBuAc=1) > 0.01 Molecular weight 62.07 a/mol Hygroscopicity : Hygroscopic.

10. STABILITY AND REACTIVITY

Chemical stability : Stable under normal conditions of use. Reacts with strong

oxidising agents.

Conditions to Avoid Incompatible Materials High Temperature.

Hazardous

Strong oxidising agents. Strong acids. Strong bases.

Decomposition Products

Thermal decomposition is highly dependent on conditions. A complex mixture of airborne solids, liquids and gases, including carbon monoxide, carbon dioxide and other organic compounds will be evolved when this material undergoes combustion or

thermal or oxidative degradation.

Possibility of Hazardous

Reactions

: Data not available.

Sensitivity to Static

Discharge

: No, product cannot ignite due to static electricity.

11. TOXICOLOGICAL INFORMATION

Information on Toxicological effects

Basis for Assessment Likely Routes of

Information given is based on product testing.

Skin and eye contact are the primary routes of exposure although exposure may occur through inhalation or following

accidental ingestion.

Acute Toxicity

Exposure

Acute Oral Toxicity : Harmful if swallowed. LD50 >300 - <=2000 mg/kg

> There is a marked difference in acute oral toxicity between rodents and man, man being more susceptible than rodents. The estimated fatal dose for man is 100 millilitres (1/2 cup). This material has also been shown to be toxic and potentially lethal

by ingestion to cats and dogs.

Acute Dermal Toxicity Expected to be of low toxicity: LD50 >5000 mg/kg

Acute Inhalation Low toxicity by inhalation.

7/10 Print Date 02.07.2014 000000001587





Toxicity

Skin Corrosion/Irritation : Slightly irritating to skin.

Serious Eye Damage/Irritation Respiratory Irritation Slightly irritating to the eye.

Repeated inhalation of vapours and mists is expected to cause

irritation of the respiratory tract.

Respiratory or skin sensitisation

Not expected to be a sensitiser.

Aspiration hazard Not considered an aspiration hazard.

Germ Cell Mutagenicity No evidence of mutagenic activity.

Carcinogenicity Not carcinogenic in animal studies.

Reproductive and **Developmental Toxicity** Does not impair fertility. Not a developmental toxicant. Causes foetotoxicity in animals; considered to be secondary to maternal

toxicity.

Specific target organ toxicity - single exposure Ingestion may cause drowsiness and dizziness. Inhalation of vapours or mists may cause irritation to the respiratory system.

Specific target organ toxicity - repeated exposure

May cause damage to organs or organ systems through prolonged or repeated exposure. Kidney: can cause kidney

damage.

12. ECOLOGICAL INFORMATION

Basis for Assessment

Ecotoxicity:

Information given is based on product testing.

Acute Toxicity

Fish Aquatic crustacea Algae/aquatic plants Microorganisms

Practically non toxic: LC/EC/IC50 > 100 mg/l Practically non toxic: LC/EC/IC50 > 100 mg/l

Practically non toxic: LC/EC/IC50 > 100 mg/l Practically non toxic: LC/EC/IC50 > 100 mg/l

Chronic Toxicity

Fish NOEC/NOEL > 100 mg/l Aquatic crustacea NOEC/NOEL > 100 mg/l

Mobility If product enters soil, one or more constituents will be mobile

and may contaminate groundwater. Dissolves in water.

Persistence/degradability

Bioaccumulative

Readily biodegradable.

Potential

Does not have the potential to bioaccumulate significantly.

13. DISPOSAL CONSIDERATIONS

Material Disposal Recover or recycle if possible. Waste arising from a spillage or

> tank cleaning should be disposed of in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand. Remove all packaging for recovery

> > 8/10

Print Date 02.07.2014 00000001587 MSDS_SG





Safety Data Sheet

or waste disposal. Do not dispose into the environment, in drains or in water courses. Waste product should not be allowed

to contaminate soil or water.

Dispose in accordance with prevailing regulations, preferably to **Container Disposal**

a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.

Local Legislation Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

14. TRANSPORT INFORMATION

Land (as per ADR classification): Not regulated

This material is not classified as dangerous under ADR regulations.

IMDG

This material is not classified as dangerous under IMDG regulations.

IATA (Country variations may apply)

This material is either not classified as dangerous under IATA regulations or needs to follow country specific requirements.

Additional Information This product may be transported under nitrogen

blanketing. Nitrogen is an odourless and invisible gas. Exposure to nitrogen may cause asphyxiation or death. Personnel must observe strict safety precautions when

involved with a confined space entry.

15. REGULATORY INFORMATION

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Chemical Inventory Status

AICS Listed. **DSL** Listed. INV (CN) Listed.

ENCS (JP) : Listed. (2)-230

TSCA : Listed.

: Listed. **EINECS** 203-473-3 KE-13169 KECI (KR) : Listed.

PICCS (PH) : Listed.

Local Regulations

Workplace Safety and Health Act & Workplace Safety and Health (General Provision) Regulations

: This product is subject to the SDS, Labelling, PEL and other

requirements in the Act/ Regulations.

Environmental Protection and Management Act and : This product is not subject to control under this Act/ Regulation.

9/10

Print Date 02.07.2014 000000001587 MSDS_SG





Safety Data Sheet

Environmental Protection

and Management

(Hazardous Substances)

Regulations

Maritime and Port Authority of Singapore (Dangerous Goods, Petroleum and

Explosives) Regulations

Fire Safety Act and Fire Safety (Petroleum & Flammable Materials)

Regulations

: This product is not subject to control under this Act/ Regulation.

: This product is not subject to control under this Act/ Regulation.

16. OTHER INFORMATION

GHS Hazard statements

H302 Harmful if swallowed.

H373 May cause damage to organs or organ systems through prolonged or repeated

exposure.

SDS Version Number : 2.0

SDS Effective Date : 25.03.2014

SDS Revisions A vertical bar (|) in the left margin indicates an amendment from

the previous version.

Uses and Restrictions : Do not use in the manufacture or preparation of foods or

pharmaceuticals.

Keep out of reach of children and pets.

Do not use in theatrical fogs or other artificial smoke generator

applications.

SDS Distribution : The information in this document should be made available to all

who may handle the product

Disclaimer This information is based on our current knowledge and is

> intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of

the product.